



## SAFETY DATA SHEET

**Severe Gear® Extreme Pressure Synthetic Racing Gear Lubricant, SAE 190, Severe Gear® Extreme Pressure Synthetic Racing Gear Lubricant, SAE 250**

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200 and WHMIS 2015, in compliance with the Hazardous Product Act (HPA, as amended) and the requirements of the Hazardous Product Regulations (HPR).

**1. Identification**
**Product identifier**

**Product name** Severe Gear® Extreme Pressure Synthetic Racing Gear Lubricant, SAE 190, Severe Gear® Extreme Pressure Synthetic Racing Gear Lubricant, SAE 250

**Product number** SRN, SRT

**Recommended use of the chemical and restrictions on use**

**Application** Lubricating oil.

**Uses advised against** Avoid the formation of mists.

**Details of the supplier of the safety data sheet**

**Supplier** AMSOIL INC.  
Bordner, Ladner, Gervais  
Scotia Plaza, 40 King St W  
Toronto, ON, Canada M5H 3Y4  
T: +1 416-367-6547

**Manufacturer** AMSOIL INC.  
One AMSOIL Center,  
Superior, WI 54880, USA.  
T: +1 715-392-7101  
compliance@amsoil.com

**Emergency telephone number**

**Emergency telephone** CHEMTREC: Within USA and Canada: 1-800-424-9300  
Outside the USA and Canada: +1 703-741-5970  
(collect calls accepted) 24/7

**2. Hazard(s) identification**
**Classification of the substance or mixture**

**OSHA/WHMIS Regulatory Status** This Product is Hazardous under the OSHA Hazard Communication Standard and according to the hazard criteria of the Hazardous Product Regulations.

**Physical hazards** Not Classified

**Health hazards** Eye Irrit. 2B - H320

**Environmental hazards** Not Classified

**Label elements**

**Signal word** Warning

**Hazard statements** H320 Causes eye irritation.

## Severe Gear® Extreme Pressure Synthetic Racing Gear Lubricant, SAE 190, Severe Gear® Extreme Pressure Synthetic Racing Gear Lubricant, SAE 250

### Precautionary statements

P264 Wash contaminated skin thoroughly after handling.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/ attention.

### Other hazards

This product does not contain any substances classified as PBT or vPvB.

### 3. Composition/information on ingredients

#### Mixtures

|  |                     |
|--|---------------------|
| <b>Polyisobutylene</b><br>CAS number: 9003-27-4  | <b>25 - &lt;50%</b> |
| <b>Classification</b><br>Eye Irrit. 2B - H320  |                     |
| <b>1-Propene, 2-methyl-, sulfurized</b><br>CAS number: 68511-50-2  | <b>2.5 - &lt;5%</b> |
| <b>Classification</b><br>Aquatic Chronic 4 - H413  |                     |
| <b>Hydrogenated base oil</b><br>CAS number: 64742-55-8   | <b>2.5 - &lt;5%</b> |
| <b>Classification</b><br>Asp. Tox. 1 - H304  |                     |
| <b>Xylene</b><br>CAS number: 1330-20-7   | <b>&lt;0.025%</b>   |
| <b>Classification</b><br>Flam. Liq. 3 - H226<br>Acute Tox. 4 - H312<br>Acute Tox. 4 - H332<br>Skin Irrit. 2 - H315<br>Eye Irrit. 2A - H319<br>STOT SE 3 - H335<br>STOT RE 2 - H373<br>Asp. Tox. 1 - H304 |                     |

## Severe Gear® Extreme Pressure Synthetic Racing Gear Lubricant, SAE 190, Severe Gear® Extreme Pressure Synthetic Racing Gear Lubricant, SAE 250

|   |                   |
|---|-------------------|
| <b>Ethylbenzene</b><br>CAS number: 100-41-4   | <b>&lt;0.025%</b> |
| <b>Classification</b><br>Flam. Liq. 2 - H225<br>Acute Tox. 4 - H332<br>STOT RE 2 - H373<br>Asp. Tox. 1 - H304<br>Aquatic Chronic 3 - H412 |                   |
| <b>Dipropylene Glycol Monomethyl Ether</b><br>CAS number: 34590-94-8  | <b>&lt;0.025%</b> |
| <b>Classification</b><br>Not Classified   |                   |

The full text for all hazard statements is displayed in Section 16.

**Composition comments**      The exact percentage is withheld as a trade secret in accordance with 29 CFR 1910.1200.

#### 4. First-aid measures

##### Description of first aid measures

|                                   |   |
|-----------------------------------|---|
| <b>General information</b>        | Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.  |
| <b>Inhalation</b>                 | Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.  |
| <b>Ingestion</b>                  | Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. |
| <b>Skin Contact</b>               | Remove affected person from source of contamination. Rinse immediately with plenty of water.  |
| <b>Eye contact</b>                | Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.   |
| <b>Protection of first aiders</b> | First aid personnel should wear appropriate protective equipment during any rescue.   |

##### Most important symptoms and effects, both acute and delayed

|                            |  |
|----------------------------|--|
| <b>General information</b> | See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure. |
| <b>Inhalation</b>          | Prolonged inhalation of high concentrations may damage respiratory system.   |
| <b>Ingestion</b>           | Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.                        |
| <b>Skin contact</b>        | Prolonged contact may cause dryness of the skin.   |
| <b>Eye contact</b>         | May cause eye irritation.  |

##### Indication of immediate medical attention and special treatment needed

## Severe Gear® Extreme Pressure Synthetic Racing Gear Lubricant, SAE 190, Severe Gear® Extreme Pressure Synthetic Racing Gear Lubricant, SAE 250

|                             |                                |
|-----------------------------|--------------------------------|
| <b>Notes for the doctor</b> | Treat symptomatically.         |
| <b>Specific treatments</b>  | No special treatment required. |

### 5. Fire-fighting measures

#### Extinguishing media

**Suitable extinguishing media** The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

#### Special hazards arising from the substance or mixture

**Specific hazards** Containers can burst violently or explode when heated, due to excessive pressure build-up. Contains Hydrocarbons. The product is immiscible with water and will spread on the water surface.

**Hazardous combustion products** Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

#### Advice for firefighters

**Protective actions during firefighting** Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves, that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.

### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

**Personal precautions** No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Use protective equipment appropriate for surrounding materials.

#### Environmental precautions

**Environmental precautions** Avoid discharge to the aquatic environment.

#### Methods and material for containment and cleaning up

**Methods for cleaning up** Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Reuse or recycle products wherever possible. Absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dispose of contents/container in accordance with national regulations.

**Reference to other sections** For personal protection, see Section 8. For waste disposal, see Section 13.

### 7. Handling and storage

#### Precautions for safe handling

## Severe Gear® Extreme Pressure Synthetic Racing Gear Lubricant, SAE 190, Severe Gear® Extreme Pressure Synthetic Racing Gear Lubricant, SAE 250

|   |   |
|---|---|
| <b>Usage precautions</b>                      | Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Avoid contact with used product. Do not reuse empty containers. |
| <b>Advice on general occupational hygiene</b> | Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.   |

### Conditions for safe storage, including any incompatibilities

|                             |   |
|-----------------------------|---|
| <b>Storage precautions</b>  | Store away from incompatible materials (see Section 10). Keep container tightly closed, in a cool, well ventilated place. Protect containers from damage. |
| <b>Storage class</b>        | Chemical storage.   |
| <b>Specific end uses(s)</b> |   |
| <b>Specific end use(s)</b>  | The identified uses for this product are detailed in Section 1.   |

### **8. Exposure Controls/personal protection**

#### Control parameters

#### Occupational exposure limits

|                 |  |
|-----------------|--|
| <b>Comments</b> | The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits. |
|-----------------|--|

Under conditions which may generate mists, the following exposure limits are recommended:

Long-term exposure limit (8-hour TWA): 5 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): 10 mg/m<sup>3</sup>

#### **Xylene**

Long-term exposure limit (8-hour TWA): OSHA 100 ppm 435 mg/m<sup>3</sup>

Long-term exposure limit (8-hour TWA): ACGIH 100 ppm 434 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): ACGIH 150 ppm 651 mg/m<sup>3</sup>

A4

#### **Ethylbenzene**

Long-term exposure limit (8-hour TWA): OSHA 100 ppm 435 mg/m<sup>3</sup>

Long-term exposure limit (8-hour TWA): ACGIH 20 ppm 87 mg/m<sup>3</sup>

A3

#### **Dipropylene Glycol Monomethyl Ether**

Long-term exposure limit (8-hour TWA): ACGIH 100 ppm 606 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): ACGIH 150 ppm 909 mg/m<sup>3</sup>

Sk

Long-term exposure limit (8-hour TWA): OSHA 100 ppm 600 mg/m<sup>3</sup>

Sk

OSHA = Occupational Safety and Health Administration.

ACGIH = American Conference of Governmental Industrial Hygienists.

A3 = Confirmed Animal Carcinogen with Unknown Relevance to Humans.

Sk = Danger of cutaneous absorption.

A4 = Not Classifiable as a Human Carcinogen.

|                            |  |
|----------------------------|--|
| <b>Ingredient comments</b> | The product contains no other substances classified as hazardous to health by an OEL value in concentrations which should be taken into account. |
|----------------------------|--|

# Severe Gear® Extreme Pressure Synthetic Racing Gear Lubricant, SAE 190, Severe Gear® Extreme Pressure Synthetic Racing Gear Lubricant, SAE 250

## Ethylbenzene (CAS: 100-41-4)

Immediate danger to life and health 800 ppm

## Dipropylene Glycol Monomethyl Ether (CAS: 34590-94-8)

Immediate danger to life and health 600 ppm

### Exposure controls

|   |  |
|---|--|
| <b>Appropriate engineering controls</b> | Provide adequate ventilation. Good general ventilation should be adequate to control worker exposure to airborne contaminants.   |
| <b>Eye/face protection</b>              | Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with OSHA 1910.133 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.6), and any relevant provincial regulation relating to health and safety at work. The following protection should be worn: Chemical splash goggles.  |
| <b>Hand protection</b>                  | Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.9), and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended. |
| <b>Other skin and body protection</b>   | Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.  |
| <b>Hygiene measures</b>                 | Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke.   |
| <b>Respiratory protection</b>           | Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Provide adequate ventilation. Large Spillages: If ventilation is inadequate, suitable respiratory protection must be worn.  |
| <b>Environmental exposure controls</b>  | Not regarded as dangerous for the environment.   |

## 9. Physical and Chemical Properties

### Information on basic physical and chemical properties

|                       |                |
|-----------------------|----------------|
| <b>Appearance</b>     | Liquid.        |
| <b>Color</b>          | Green.         |
| <b>Odor</b>           | Sulfur.        |
| <b>Odor threshold</b> | Not available. |
| <b>pH</b>             | Not available. |

## Severe Gear® Extreme Pressure Synthetic Racing Gear Lubricant, SAE 190, Severe Gear® Extreme Pressure Synthetic Racing Gear Lubricant, SAE 250

|   |   |
|---|---|
| <b>Melting point</b>                                | Not available.  |
| <b>Initial boiling point and range</b>              | Not available.  |
| <b>Flash point</b>                                  | 210 - 214°C Cleveland open cup. [ASTM D 92]                         |
| <b>Evaporation rate</b>                             | Not available.  |
| <b>Upper/lower flammability or explosive limits</b> | Not available.  |
| <b>Vapor pressure</b>                               | Not available.  |
| <b>Vapor density</b>                                | Not available.  |
| <b>Relative density</b>                             | 0.8800 - 0.8833   |
| <b>Solubility(ies)</b>                              | Not known.  |
| <b>Partition coefficient</b>                        | Not available.  |
| <b>Auto-ignition temperature</b>                    | Not available.  |
| <b>Decomposition Temperature</b>                    | Not available.  |
| <b>Viscosity</b>                                    | 364.7 - 494.5 cSt @ 40°C<br>37.3 - 47.0 cSt @ 100°C<br>[ASTM D 445] |
| <b>Explosive properties</b>                         | Not considered to be explosive.                                     |
| <b>Oxidizing properties</b>                         | Does not meet the criteria for classification as oxidizing.         |
| <b>Fire point</b>                                   | 222 - 226°C Cleveland open cup. [ASTM D 92]                         |
| <b>Pour point</b>                                   | -24 - (-31)°C [ASTM D 97]   |

### 10. Stability and reactivity

|   |   |
|---|---|
| <b>Reactivity</b>                         | See the other subsections of this section for further details.  |
| <b>Stability</b>                          | Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.   |
| <b>Possibility of hazardous reactions</b> | No potentially hazardous reactions known.   |
| <b>Conditions to avoid</b>                | There are no known conditions that are likely to result in a hazardous situation.   |
| <b>Materials to avoid</b>                 | No specific material or group of materials is likely to react with the product to produce a hazardous situation.  |
| <b>Hazardous decomposition products</b>   | Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors. |

### 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity - oral

**Notes (oral LD<sub>50</sub>)** Based on available data the classification criteria are not met.

#### Acute toxicity - dermal

## Severe Gear® Extreme Pressure Synthetic Racing Gear Lubricant, SAE 190, Severe Gear® Extreme Pressure Synthetic Racing Gear Lubricant, SAE 250

|  |   |
|--|---|
| <b>Notes (dermal LD<sub>50</sub>)</b>                            | Based on available data the classification criteria are not met.  |
| <b><u>Acute toxicity - inhalation</u></b>                        |   |
| <b>Notes (inhalation LC<sub>50</sub>)</b>                        | Based on available data the classification criteria are not met.  |
| <b><u>Skin corrosion/irritation</u></b>                          |   |
| <b>Animal data</b>   | Based on available data the classification criteria are not met.  |
| <b><u>Serious eye damage/irritation</u></b>                      |   |
| <b>Serious eye damage/irritation</b>                             | Causes eye irritation.  |
| <b><u>Respiratory sensitization</u></b>                          |   |
| <b>Respiratory sensitization</b>                                 | Based on available data the classification criteria are not met.  |
| <b><u>Skin sensitization</u></b>                                 |   |
| <b>Skin sensitization</b>  | Based on available data the classification criteria are not met.  |
| <b><u>Germ cell mutagenicity</u></b>                             |   |
| <b>Genotoxicity - in vitro</b>                                   | Based on available data the classification criteria are not met.  |
| <b><u>Carcinogenicity</u></b>                                    |   |
| <b>Carcinogenicity</b>   | Based on available data the classification criteria are not met.  |
| <b>IARC carcinogenicity</b>                                      | None of the ingredients are listed or exempt.   |
| <b><u>Reproductive toxicity</u></b>                              |   |
| <b>Reproductive toxicity - fertility</b>                         | Based on available data the classification criteria are not met.  |
| <b>Reproductive toxicity - development</b>                       | Based on available data the classification criteria are not met.  |
| <b><u>Specific target organ toxicity - single exposure</u></b>   |   |
| <b>STOT - single exposure</b>                                    | Not classified as a specific target organ toxicant after a single exposure.   |
| <b><u>Specific target organ toxicity - repeated exposure</u></b> |   |
| <b>STOT - repeated exposure</b>                                  | Not classified as a specific target organ toxicant after repeated exposure.   |
| <b><u>Aspiration hazard</u></b>                                  |   |
| <b>Aspiration hazard</b>   | Based on available data the classification criteria are not met.  |
| <b><u>General information</u></b>                                |   |
| <b>General information</b>                                       | The severity of the symptoms described will vary dependent on the concentration and the length of exposure.                                       |
| <b>Inhalation</b>  | Prolonged inhalation of high concentrations may damage respiratory system.  |
| <b>Ingestion</b>   | Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation. |
| <b>Skin Contact</b>  | Prolonged contact may cause dryness of the skin.  |
| <b>Eye contact</b>   | May cause eye irritation.   |
| <b>Route of exposure</b>   | Ingestion Inhalation Skin and/or eye contact  |
| <b>Target Organs</b>   | No specific target organs known.  |
| <b>Medical considerations</b>                                    | Skin disorders and allergies.   |

### 12. Ecological Information



## Severe Gear® Extreme Pressure Synthetic Racing Gear Lubricant, SAE 190, Severe Gear® Extreme Pressure Synthetic Racing Gear Lubricant, SAE 250

|   |   |
|---|---|
| <b>Ecotoxicity</b>                          | Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment. |
| <b>Toxicity</b>                             | Based on available data the classification criteria are not met.  |
| <b><u>Persistence and degradability</u></b> |   |
| <b>Persistence and degradability</b>        | The degradability of the product is not known.  |
| <b><u>Bioaccumulative potential</u></b>     |   |
| <b>Bio-Accumulative Potential</b>           | No data available on bioaccumulation.   |
| <b>Partition coefficient</b>                | Not available.  |
| <b><u>Mobility in soil</u></b>              |   |
| <b>Mobility</b>                             | No data available.  |
| <b><u>Other adverse effects</u></b>         |   |
| <b>Other adverse effects</b>                | None known.   |

### 13. Disposal considerations

#### **Waste treatment methods**

|                            |   |
|----------------------------|---|
| <b>General information</b> | The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. |
| <b>Disposal methods</b>    | Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste packaging should be collected for reuse or recycling. Incineration or landfill should only be considered when recycling is not feasible. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of the local water authority.                          |

### 14. Transport information

|  |   |
|--|---|
| <b>General</b>                             | The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, DOT, TDG). |
| <b><u>UN Number</u></b>                    |   |
| Not applicable.                            |   |
| <b><u>UN proper shipping name</u></b>      |   |
| Not applicable.                            |   |
| <b><u>Transport hazard class(es)</u></b>   |   |
| <b><u>Transport labels</u></b>             |   |
| No transport warning sign required.        |   |
| <b><u>Packing group</u></b>                |   |
| Not applicable.                            |   |
| <b><u>Environmental hazards</u></b>        |   |
| <b>Environmentally Hazardous Substance</b> |   |
| No.  |   |

## **Severe Gear® Extreme Pressure Synthetic Racing Gear Lubricant, SAE 190, Severe Gear® Extreme Pressure Synthetic Racing Gear Lubricant, SAE 250**

### **Special precautions for user**

Not applicable.

**DOT TIH Zone** Not applicable.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

### **15. Regulatory information**

**Regulatory References** OSHA Hazard Communication Standard 29 CFR §1910.1200 Hazardous Products Regulation (SOR/2015-17) Transportation of Dangerous Goods Regulations -SOR/2015-100.

### **US Federal Regulations**

#### **SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities**

None of the ingredients are listed or exempt.

#### **CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)**

The following ingredients are listed or exempt:

*Xylene*

Final CERCLA RQ: 100(45.4) pounds (Kilograms)

*Ethylbenzene*

Final CERCLA RQ: 1000(454) pounds (Kilograms)

#### **SARA Extremely Hazardous Substances EPCRA Reportable Quantities**

None of the ingredients are listed or exempt.

#### **SARA 313 Emission Reporting**

The following ingredients are listed or exempt:

*Xylene*

0.1 %

1.0 %

*Ethylbenzene*

0.1 %

#### **CAA Accidental Release Prevention**

None of the ingredients are listed or exempt.

#### **SARA (311/312) Hazard Categories**

None of the ingredients are listed or exempt.

#### **OSHA Highly Hazardous Chemicals**

None of the ingredients are listed or exempt.

### **US State Regulations**

#### **California Proposition 65 Carcinogens and Reproductive Toxins**

The following ingredients are listed or exempt:

*Ethylbenzene*

Known to the State of California to cause cancer.

#### **California Air Toxics "Hot Spots" (A-I)**

The following ingredients are listed or exempt:

## **Severe Gear® Extreme Pressure Synthetic Racing Gear Lubricant, SAE 190, Severe Gear® Extreme Pressure Synthetic Racing Gear Lubricant, SAE 250**

*Xylene*

*Ethylbenzene*

*Dipropylene Glycol Monomethyl Ether*

### **California Air Toxics "Hot Spots" (A-II)**

None of the ingredients are listed or exempt.

### **California Directors List of Hazardous Substances**

The following ingredients are listed or exempt:

*Xylene*

*Ethylbenzene*

*Dipropylene Glycol Monomethyl Ether*

### **Massachusetts "Right To Know" List**

The following ingredients are listed or exempt:

*Xylene*

*Ethylbenzene*

*Dipropylene Glycol Monomethyl Ether*

### **Rhode Island "Right To Know" List**

The following ingredients are listed or exempt:

*Xylene*

*Ethylbenzene*

*Dipropylene Glycol Monomethyl Ether*

### **Minnesota "Right To Know" List**

The following ingredients are listed or exempt:

*Xylene*

*Ethylbenzene*

*Dipropylene Glycol Monomethyl Ether*

### **New Jersey "Right To Know" List**

The following ingredients are listed or exempt:

*Xylene*

*Ethylbenzene*

*Dipropylene Glycol Monomethyl Ether*

### **Pennsylvania "Right To Know" List**

The following ingredients are listed or exempt:

*Xylene*

*Ethylbenzene*

*Dipropylene Glycol Monomethyl Ether*

### **Inventories**

#### **Canada - DSL/NDSL**

All the ingredients are listed or exempt.

## Severe Gear® Extreme Pressure Synthetic Racing Gear Lubricant, SAE 190, Severe Gear® Extreme Pressure Synthetic Racing Gear Lubricant, SAE 250

### US - TSCA

All the ingredients are listed or exempt.

### US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

## 16. Other information

|   |   |
|---|---|
| <b>Abbreviations and acronyms used in the safety data sheet</b> | C.A.S. = Chemical Abstracts Service; E.C. No = European Commission number; GHS = Globally Harmonised System; OSHA = Occupational Safety and Health Administration; WHMIS = Workplace Hazardous Materials Information System; DOT = Department of Transport; TDG = Transport of Dangerous Goods Regulations; IMDG = International Maritime Dangerous Goods; IATA = International Air Transport Association; SARA = Superfund Amendments and Reauthorization Act; CERCLA = Comprehensive Environmental; EPCRA = Emergency Planning and Community Right-to-Know Act; TSCA = Toxic Substances Control Act; LD/LC/EC = Lethal Dose, Lethal Concentration/Effect Concentration for 50% of population; NOEC = No Overall Effect Concentration; NOEL = No Overall Effect Level; REACH = Registration, Evaluation, Authorisation & Restriction of Chemicals; STOT-RE = Single Target Organ Toxicity - Repeat Exposure; STOT-SE = Specific Target Organ Toxicity - Single Exposure; PBT = Persistent, Bioaccumulative, Toxic; vPvB = Very Persistent, Very Bioaccumulative. |
| <b>Key literature references and sources for data</b>           | Source: European Chemicals Agency, <a href="http://echa.europa.eu/">http://echa.europa.eu/</a>  |
| <b>Training advice</b>  | Read and follow manufacturer's recommendations. Only trained personnel should use this material.  |
| <b>Revision comments</b>  | This is first issue.  |
| <b>Revision date</b>  | 12/6/2017   |
| <b>SDS No.</b>  | 6509  |
| <b>Hazard statements in full</b>                                | <p>H225 Highly flammable liquid and vapor.</p> <p>H226 Flammable liquid and vapor.</p> <p>H304 May be fatal if swallowed and enters airways.</p> <p>H312 Harmful in contact with skin.</p> <p>H315 Causes skin irritation.</p> <p>H319 Causes serious eye irritation.</p> <p>H320 Causes eye irritation.</p> <p>H332 Harmful if inhaled.</p> <p>H335 May cause respiratory irritation.</p> <p>H373 May cause damage to organs (Central nervous system, Liver, Kidneys) through prolonged or repeated exposure.</p> <p>H373 May cause damage to organs (Hearing organs) through prolonged or repeated exposure.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p> <p>H413 May cause long lasting harmful effects to aquatic life.</p>   |

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.